



AOPEN

Bright Ideas Connected

Digital Engine®



Powerful and Breathtaking Large Splicing Wall Solution **DEV7610-X6**

The DEV7610-X6 takes computing power to a whole new level! It has the computing power to support high-end multi-screen Splicing Wall Solution. It is designed with a PCI Express Card slot for endless transportation and surveillance applications. DEV7610-X6 came to reshape Digital Signage and Video Wall Solution.

Features

- + The latest 8th generation Intel Core i platform with Desktop CPU
- + Equipped with AMD E8860 GPU Module to implement video wall application
- + Compatibility to support HDD and SSD storage devices
- + Redundant and reliable 24/7 operation
- + Slim form factor chassis with aluminum front panel design for commercial applications

DEV7610-X6



Line out Mic in Type-C USB3.1 Gen2 USB3.0 Power Button



Mini Display Port x 6 Display Port HDMI 1.4 USB 3.0 USB 2.0 Power in DC

Model name		DEV7610-X6
Weight	3.8L	
Dimension W×H×D(mm)	300 x 212 x 60 mm	
CPU	Socket	LGA1151
	Type	Intel Pentium/ Celeron/ 8th Generation Core i3/5/7 CPU
Chipset	Intel Lake B360	
Memory	Channel	Dual Channel
	Type	DDR4 SO DIMM x 2
	DDR	2400/2666
	Max Memory	32GB
Graphic	AMD (Radeon E8860 GPU)	
Audio	Type	Realtek ALC269 5.1 Channel HDA Codec
	Channel	Line Out x 1, Mic in x 1
Power Adapter	180 W	
Output	Mini DP x 6	

Video	Display Port x 1, HDMI x 1	
Expansion slot	Mini Card Slot	M.2 2280 PCI-E SSD Slot M.2 2242 PCI-E Slot M.2 2280 Intel Optane Memory Slot
	LAN	RJ45 x 1, 10/100/1000 Mbps
USB Port	USB2.0 x 2 (Rear) USB3.0 x 3 (Front x 1, Rear x 2) USB3.1 Gen2 x 1 (Front) USB Type C x 1 (Front)	
Storage	2.5"SATA HDD x 1 M.2 2280 SSD M.2 2280 Intel Optane Memory Slot	
Watchdog Timer	N/A	
OS	Windows 10, Linux	
Environment		
Operating Temperature	0~45°C (32~113°F)	
Storage Temperature	-20~60°C (-4~140°F)	
Relative Humidity	95% RH	

Support :

